

# Enclosed general purpose trolley

P/N: 0111934 | GSW 8x5/2

**HUPFER**  
we make work flow



## Technical data

<b>Capacity:</b>	2 Borde
<b>Payload:</b>	80 kg
<b>Weight:</b>	33 kg
<b>Width:</b>	900 mm
<b>Depth:</b>	600 mm
<b>Height:</b>	950 mm

*Similar to illustration, technical modifications reserved. Without decoration.*

Serving trolley in closed version with deep-drawn shelves.

Wagen in stabiler, selbsttragender und hygienischer Konstruktion aus hochwertigem Edelstahl. Rundrohrrahmen  $\varnothing$  25 mm mit 2 fest eingeschweißten, tiefgezogenen Borden  $800 \times 500$  mm mit 10 mm hohem Profilrand, schalldämmend unterfüttert, hygienisch um 35 mm abgekantet und nach innen gefalzt, in reinigungsfreundlicher Ausführung. Beidseitige, in den Rohrrahmen integrierte Schiebebügel sorgen für leichte Manövrierbarkeit. Wagen mit dreiseitiger Edelstahl-Verkleidung und-Flügeltüren mit Grifföffnung und Magnetverschluss. 4 Abweiserrollen aus Polypropylen dienen als Anfahrerschutz, schützen sowohl den Wagen rundum als auch bauseitige Wände vor Beschädigungen. Wagen fahrbar auf 4 Lenkrollen, 2 mit Totalfeststellern,  $\varnothing$  125 mm, Gehäuse verzinkt-chromatisiert, Kunststoffrad mit Rollenlager, luftdichteste und pannensichere Lauffläche, mit Zapfenbefestigung.

The Hupfer serving trolley GSW 8x5/2 is a welded model delivered ready for use, and provides full stainless steel panelling, including doors. The smooth and cavity-free raised edges makes this model easy to clean, and prevents dirt from accumulating in the corners. The air-free and puncture-proof tyres ensure running noises are kept to a minimum, and make it especially suitable for uneven flooring.

Time and date of the request: 31.01.2025, 00:34:21 *All information / dimensions are approximate, technical changes reserved. © Hupfer*