NORM35 upright

P/N: 0126012 | RG-RS/N35 1800/610





Technical data

Modular dimension: 150 mm

Max. section load 2000

Carbon footprint (TM65 Basic Report) 96 kgCO□e

 Weight:
 10 kg

 Width:
 610 mm

 Depth:
 30 mm

Height: 1800 mm

Similar to illustration, technical modifications reserved. Without decoration.

Modular shelving system made of high-quality stainless steel in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140 $^{\circ}$ F (-40 to +60 $^{\circ}$ C), for stand-alone placement, freely extendable lengthwise.

Uprights made of 1. 2×1 . 2'' (30 \times 30 mm) square tubes, connected by welded upright spokes made of $2.4 \times 0.16''$ (60 \times 4.0 mm) flat profiles that also serve as possibility for permanently attaching shelves. Additional attachment options through shelf lugs that are welded to the uprights in a 5.9" (150 mm) grid, enabling two included hook-on elements per upright to be attached variably. Upper covering caps made of plastic and height-adjustable aluminium screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright.

Time and date of the request: 10.04.2025, 20:15:42

All information / dimensions are approximate, technical changes reserved. © Hupfer