

## Basket dispenser with fan-assisted cooling

P/N: 0161450 | BDC/UK 50-50



*Similar to illustration, technical modifications reserved. Without decoration.*

### Technical data

<b>Capacity:</b>	4 Körbe 115 mm hoch o.7 Körbe 75 mm hoch
<b>Payload:</b>	100 kg
<b>Capacity:</b>	550 W
<b>Cooling capacity:</b>	400 Watt
<b>Supply voltage:</b>	AC 220-230 V
<b>Nominal current:</b>	2.40 A
<b>Protection class:</b>	Klasse 1
<b>Frequency:</b>	50-60 Hz
<b>Weight:</b>	102.038 kg
<b>Width:</b>	1092 mm
<b>Depth:</b>	760 mm
<b>Height:</b>	900 mm

Closed basket dispenser cooled with circulating air, with height-adjustable platform for storing and cooling 19.7 × 19.7" (500 × 500 mm) or 20.0 × 20.0" (508 × 508 mm) baskets with portioned cold meals or crockery items for cold meals.

Dispenser in self-supporting and hygienic design, made of high-quality stainless steel. Closed, smooth outer housing with thermal insulation through high-quality special insulation. Open stacking compartment with removable basket that can be included in the stacking capacity, made of plastic-coated stainless steel as stacking platform with ball bearing platform guide. Consistent output height thanks to manually adjustable stainless steel tension spring system. Easy cleaning of stacking compartment from above and via a closable cleaning opening in the base plate. Reduced energy losses through double-walled and insulated stainless steel cover hood with silicone seal and clamp. Convection cooling with CFC-free refrigerant and all-round tubing to ensure a uniform temperature distribution, to be operated using On/Off switch with integrated indicator light. Current supply via dimensionally stable and extractable spiral cable with angle plug. Dummy socket in switch plate as plug park. Four massive polymer corner bumpers, of which two at the upper corners of the structure that serve as bumpers and protect the equipment on all sides as well as building-side walls from being damaged, with integrated, ergonomically-shaped push bars. Dispenser runs on 4 swivel casters of which 2 with total locks,  $\varnothing$  4.9" (125 mm), fastened by means of screw-on plates and several screws.

Time and date of the request: 22.12.2024, 02:28:53 *All information / dimensions are approximate, technical changes reserved. © Hupfer*

## Basket dispenser with fan-assisted cooling

P/N: 0161450 | BDC/UK 50-50

**HUPFER**  
we make work flow

The Hupfer cool dispenser® BDC/UK 50-50 has the smallest external dimensions and the lowest empty weight in comparison to other products, while two push handles installed on the corners of the unit ensure optimal handling properties. The ergonomically shaped push handles also guarantee effective protection against injuries to the hands. The installation height of 900 mm is the standard working height in food distribution. The guide basket, which comes as series standard, is the same as the non-rusting, stainless steel crockery baskets available as an optional accessory, and increases the stacking capacity by approx. 20 %.

Time and date of the request:  
22.12.2024, 02:28:53

*All information / dimensions are approximate, technical changes reserved. © Hupfer*