

Fan-heated basket dispenser

P/N: 0161700 | KO/UH 65-53

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

| | |
|---------------------------|------------------------------------|
| Capacity: | 6 Körbe 115 mm, 9 Körbe 75 mm hoch |
| Temperature range: | analogue controller, stepless |
| Payload: | 200 kg |
| Capacity: | 2000 W |
| Supply voltage: | AC 220-230 V |
| Nominal current: | 8.70 A |
| Protection class: | Klasse 1 |
| Frequency: | 50-60 Hz |
| Weight: | 69 kg |
| Width: | 992 mm |
| Depth: | 760 mm |
| Height: | 1082 mm |

Closed basket dispenser heated with circulating air, with height-adjustable platform for storing 25.6 × 20.9" (650 × 530 mm) baskets with small or difficult-to-stack crockery items.

Dispenser in self-supporting and hygienic design, made of high-quality stainless steel. Closed, smooth outer housing with thermal insulation through high-quality special insulation. Inner panelling on all sides, with high-quality mirror sheets for optimised energy usage. Open stacking compartment with removable basket that can be included in the stacking capacity, made of plastic-coated stainless steel as stacking platform with ball bearing platform guide. Consistent output height thanks to manually adjustable stainless steel tension spring system. Easy cleaning of stacking compartment from above and via a cleaning opening in the base plate. Reduced temperature losses and heating time thanks to cover hood made of grey polymer. Heated by power module with integrated motor, fan impeller and stainless steel tubular heating element for automatic convection air operation, operated using On/Off switch with integrated indicator light, thermostat-controlled using a continuously variable, ergonomically-shaped thermostat that is easy to read even from a distance, with temperature limiter as per VDE. Current supply via dimensionally stable and extractable spiral cable with angle plug. Dummy socket in switch plate as plug park. Four massive polymer corner bumpers, of which two at the upper corners of the structure that serve as bumpers and protect the equipment on all sides as well as building-side walls from being damaged, with integrated, ergonomically-shaped push bars. Dispenser runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), fastened by means of screw-on plates and several screws.

Time and date of the request: 19.11.2024, 23:12:30 *All information / dimensions are approximate, technical changes reserved. © Hupfer*

Fan-heated basket dispenser

P/N: 0161700 | KO/UH 65-53

HUPFER
we make work flow

The Hupfer basket dispenser KO/UH 65-53 has the lowest empty weight in comparison to other products, while two push handles installed on the corners of the unit ensure optimal handling properties. The ergonomically shaped push handles also guarantee effective protection against injuries to the hands. The installation height of 900 mm is the standard working height in food distribution. The guide basket, which comes as series standard, is the same as the non-rusting, stainless steel crockery baskets available as an optional accessory, and increases the stacking capacity by approx. 20 %.

Time and date of the request:
19.11.2024, 23:12:30

All information / dimensions are approximate, technical changes reserved. © Hupfer