Incounter plate dispenser, heated



P/N: 0162251 | EB-TE H



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Capacity: bis zu 44 Teile o. Haube, 52 m. Haube

Payload: 60 kg Capacity: 600 W

Supply voltage: AC 220-230 V

Nominal current: 2,6 A

Protection class: Class I

Frequency: 50/60 Hz

Weight: 16.023 kg

Width: 470 mm

Depth: 470 mm

Height: 820 mm

Plate dispenser for installation into a worktop, for storing \emptyset 10.6-13.0" (180-330 mm) round plates in a statically heated stacking compartment.

Dispenser in robust and hygienic design, made of high-quality stainless steel. Closed design for installation from above with shelf frame. Open stacking compartment and one stacking platform in plastic-coated rod design to prevent crockery discolourations. Stacking compartment with three plastic-coated crockery guides, variably adjustable without tools. Consistent output height thanks to manually adjustable stainless steel tension spring system. Easy cleaning of stacking compartment from above and via a cleaning opening in the base plate. Reduced temperature losses and heating time thanks to cover hood made of polycarbonate with 3-point locking mechanism. Heating through stainless steel tubular heating element, infinitely variable using thermostat toggle switch on the equipment, with temperature limiter as per VDE. Current supply via a connecting cable set consisting of two connecting cables with earthed plug and equipment plug and an On/Off switch with integrated indicator light as disconnector.

The Hupfer incounter plate dispenser EBR-TE/H 18-33 has an adjustable guide that protrudes 57 mm above the support frame and which can be fixed in a base plate, and the use of non-rusting stainless steel springs that are easy to insert and remove provides optimal adjustment options for different crockery diameters and loads. The vertical installation of the three heating elements ensures a particularly uniform distribution of heat. The on/off switch can be conveniently integrated into the worktop and requires a cut-out measuring 30×22 mm.

Time and date of the request: 26.04.2025, 22:26:56

All information / dimensions are approximate, technical changes reserved. © Hupfer