

Platform dispenser

P/N: 0162988 | BD/UH 60-60 4S

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Capacity:	bis zu 306 Teile o. Haube, 372 m. Haube
Temperature range:	analogue controller, stepless
Payload:	200 kg
Capacity:	2000 W
Supply voltage:	AC 220-230 V
Nominal current:	8.70 A
Frequency:	50-60 Hz
Weight:	92.239 kg
Width:	991 mm
Depth:	760 mm
Height:	1080 mm

Closed platform dispenser heated with circulating air, with height-adjustable platform for storing up to 16 stacks of \varnothing 5.5-11.8" (140-300 mm) round crockery items and rectangular crockery items with edge lengths of 6.3-10.6" (160-270 mm).

Dispenser in self-supporting and hygienic design, made of high-quality stainless steel. Closed, smooth outer housing with thermal insulation through high-quality special insulation. Inner panelling on all sides, with high-quality mirror sheets for optimised energy usage. Stacking compartment including compartment inner panelling consisting of vertical plastic-coated struts. Removable platform made of high-quality stainless steel, with ball bearing platform guide. Consistent output height thanks to manually adjustable stainless steel tension spring system. Easy cleaning of stacking compartment from above. Reduced temperature losses and heating time thanks to cover hood made of grey polypropylene. Heated by power module with integrated motor, fan impeller and stainless steel tubular heating element for automatic convection air operation, operated using On/Off switch with integrated indicator light, thermostat-controlled using a continuously variable, ergonomically-shaped thermostat that is easy to read even from a distance, with temperature limiter as per VDE. Current supply via dimensionally stable and extractable spiral cable with angle plug. Dummy socket in switch plate as plug park. Four massive polymer corner bumpers, of which two at the upper corners of the structure that serve as bumpers and protect the equipment on all sides as well as building-side walls from being damaged, with integrated, ergonomically-shaped push bars. Dispenser runs on 4 swivel casters of which 2 with total locks, \varnothing 4.9" (125 mm), fastened by means of screw-on plates and several screws.

Time and date of the request: 22.12.2024, 11:04:18 *All information / dimensions are approximate, technical changes reserved. © Hupfer*

Platform dispenser

P/N: 0162988 | BD/UH 60-60 4S

HUPFER
we make work flow

The Hupfer platform dispenser BD/UH 60-60 4S has the largest usable stacking space in comparison to other products, while two push handles installed on the corners of the unit ensure optimal handling properties. The ergonomically shaped push handles also guarantee effective protection against injuries to the hands. The installation height of 900 mm is the standard working height in food distribution.

Time and date of the request:
22.12.2024, 11:04:18

All information / dimensions are approximate, technical changes reserved. © Hupfer