

Köhler banquet trolley, heated, with passive cooling



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Capacity: $14 + 5 \times \text{Rost oder Behälter GN 1/1}$

Modular dimension: 57.5 mm

Insertion type: Lengthwise insertion

 Payload:
 95 kg

 Capacity:
 1600 W

Supply voltage: AC 220-230 V

Nominal current: 6,9 A

Protection class: Class I

Frequency: 50/60 Hz

Weight: 147 kg

Width: 640 mm **Depth:** 775 mm

Height: 1857 mm

Banquet trolley for holding constituents of meals on GN 1/1 gratings or in GN 1/1 containers with lid.

Trolley made entirely of high-quality stainless steel, self-supporting design. Double-walled banquet trolley, closed on all sides, wall and doors thermally insulated CFC-free. Double-walled double-wing doors with spring-supported door lock made of plastic, can be opened single-handed by 270°. Automatic door blocking when closed or open. Easy cleaning of trolleys. Interior of base and upper section with two removable shelf uprights with L-shaped shelf rails each, plus additional insertion option for one GN 1/1 eutectic plate in the upper section. Heating of base through removable thermal module that automatically locks in place when inserted, infinitely variable. Maximum temperature attainable within 25 minutes. Efficient convection heating with integrated hot damp air system, including humidification pan, sufficient for approx. 3.5 hours of operation, ensures optimum retention of temperature and taste. Prevention of heat losses thanks to removable special sealing profiles. Thermal partition between base and upper section. Temperature control using thermostat with analogue display in double-wing door. Upper neutral compartment can be cooled using cold storage plate, temperature control also via analogue thermometer in door. Four continuous vertical push bars (2 on each side), for manoeuvring even with the door open. Bumper protective feature provided by continuous bumper frame at bottom and top of trolley and additionally between the two compartments, effective also when door is

Time and date of the request: 25.04.2025, 01:13:02

All information / dimensions are approximate, technical changes reserved. © Hupfer



Köhler banquet trolley, heated, with passive cooling

open. Trolley runs on 2 swivel casters with total locks and 2 fixed casters, Ø 4.9" (125 mm), fastened by means of screw-on plates and several screws.

The Hupfer banquet trolley BKW 1 / 14 L-GN-57,5 +5PK has four vertical push bars to ensure effortless handling by persons of any size even when the door is open, and the use of removable tray racks ensures optimal cleaning results, while the clearance between the sides of the racks and the side panels of the trolley ensures improved air circulation. In addition, this module provides a combination of a heated lower compartment and a passively cooled upper neutral compartment.

Time and date of the request: 25.04.2025, 01:13:02

All information / dimensions are approximate, technical changes reserved. © Hupfer