

## Transport cart for 30 EN trays

P/N: 0164654 | TTW/V 3/30 EN 115-L PK

### Technical data



<b>Modular dimension:</b>	115 mm
<b>Insertion type:</b>	Lengthwise insertion
<b>Payload:</b>	100 kg
<b>Weight:</b>	173 kg
<b>Width:</b>	1537 mm
<b>Depth:</b>	777 mm
<b>Height:</b>	1646 mm

*Similar to illustration, technical modifications reserved. Without decoration.*

#### Insulated cart for transporting food on trays

Fully enclosed, double-wall insulated stainless steel transport cart. The design and materials are chosen to ensure many years of hard daily use. Smooth surfaces on the outside and inside of the cart allow hygienic cleaning. All-round polymer bumper strips on the chassis and roof effectively protect the cart from damage. DIN-quality wheels and four push bars enable easy handling of the cart. Well-sealed doors and completely insulated housing ensure that the cold chain is maintained and HACCP temperature requirements are met. With a wide range of equipment options, the cart can be adapted to individual requirements. For maximum hygienic requirements, the transport trolley interior is fully seal-welded and seamless. Together with high-quality, corrosion-resistant wheels, the transport cart is suitable for cleaning in washing devices.

Time and date of the request: 04.03.2025, 15:49:31 *All information / dimensions are approximate, technical changes reserved. © Hupfer*