

P/N: 0191443702 | LR Poly/St RI2/125 luftid mF sw



Technical data

Payload:	75 kg
Weight:	0.4 kg
Width:	130 mm
Depth:	59 mm
Height:	161 mm

Similar to illustration, technical modifications reserved. Without decoration.

The swivel castor is used for attachment to mobile devices. The swivel castor allows for the mobility, steerability, and controllability of the devices.

The smooth-running swivel castor made of high-quality plastic with zinc-coated steel components is corrosionresistant and is designed for attachment to mobile equipment. The Hupfer swivel castor ensures the mobility of mobile devices. The effortless turning, steering, and positioning of the equipment using the swivel castors increase the efficiency and safety of task execution in tight or crowded work areas. The robust swivel castor is equipped with a swivel bearing with a double ball race and allows for easy handling of the equipment, even with heavy loads. The air-identical wheel combines the smoothness of air tires with the robustness of solid rubber tires. The precision ball bearing enables nearly silent and frictionless mobility. The swivel castor is securely mounted to the device using a rear hole, providing stability.

- Durable plastic housing ensures longevity
- Swivel bearings with double ball race allow effortless movement and precise control
- Air-identical wheel provides smooth operation and robustness
- Ball bearings ensure near-silent and smooth maneuverability

Time and date of the request:All information / dimensions are approximate, technical changes reserved. © Hupfer05.04.2025, 03:48:34