

# NORM20/12 upright

P/N: 0201327 | RG-RS/N20/12 600kg 2000/600

**HUPFER**  
we make work flow



## Technical data

<b>Modular dimension:</b>	150 mm
<b>Max. section load</b>	600
<b>Carbon footprint (TM65 Basic Report)</b>	79 kgCO <sub>2</sub> e
<b>Weight:</b>	3 kg
<b>Width:</b>	25 mm
<b>Depth:</b>	1950 mm
<b>Height:</b>	604 mm

*Similar to illustration, technical modifications reserved. Without decoration.*

Modular shelving system made of natural anodised aluminium in a hygienic design as per DIN 18868-2, suitable for continuous use at -40 °C to + 60 °C, for installation in a straight line or as a corner unit with corner hooks, extendable to any length.

Uprights made of special 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 1.6 × 0.28" (40 × 7 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded shelf lugs at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request:  
04.04.2025, 19:11:37

*All information / dimensions are approximate, technical changes reserved. © Hupfer*