

## Känguruh push-in rack

P/N: 7504620 | KÄ-EG 6StE 685/615/1041 3 DR

### Technical data



**Capacity:** 6 × StE mit 3 Drahtrostauflagen

**Weight:** 15.577 kg

**Width:** 685 mm

**Depth:** 615 mm

**Height:** 1041 mm

*Similar to illustration, technical modifications reserved. Without decoration.*

Rack frame for storing sterilisation units.

Rack in robust, self-supporting, hygienic and sterilisable design, made of high-quality stainless steel square tubes with two welded wire shelves and one wire shelf that can be hooked in loosely in the lower section. Safe connection of rack and receiving system component (transport trolley, transfer dolly or base frame) by means of a locking wire that is released by lifting at the upper side of the rack. Once the rack has been retracted until it has reached the locking point and the wire is let loose, the wire latches safely and audibly into an anchor block. Two guide rails, made of stainless steel sheet and arranged centrally in longitudinal direction underneath the rack, provide additional safety along with matching guide rollers at the relevant system component. Mobile rack frame runs on 4 sterilisable fixed casters with  $\varnothing$  3.0" (75 mm) caster body made of polymer.

Time and date of the request:  
20.11.2024, 18:34:35

*All information / dimensions are approximate, technical changes reserved. © Hupfer*