

Fully-welded sterile goods transport cart

P/N: 7505984 | STW/VV 3StE 724/754/1445



Technical data

Cleaning classification:	Waschanlagentauglich
Capacity:	3 × StE
Modular dimension:	61.5 mm
Payload:	200 kg
Width:	724 mm
Depth:	754 mm
Height:	1445 mm

Similar to illustration, technical modifications reserved. Without decoration.

Transport cart for the transport and storage of sterile goods in containers or baskets. Stainless steel wheel 160 mm as standard. Including sign holder.

Cart made entirely of high-quality stainless steel, stable, self-supporting and hygienic construction. Single-walled, fully enclosed cart body in fully welded, wash-down suitable design. Reinforcement of the cart roof through upward cross bracing. Double-walled swing doors with continuous seals that open 270°, automatic locking mechanism, operable with one hand. Door lock via integrated 2-point locking system. Interior with removable and height-adjustable closed pads across the entire interior height. Four vertical push rods (2 on each side) for maneuvering even with the doors open. Impact protection through a sturdy continuous bumper strip with end cut-outs for any towing device on the chassis, effective even with the doors open. Cart movable on 2 swivel castors with total brake, 2 fixed castors, secured with multiple screwed mounting plates.

Time and date of the request:
11.04.2025, 06:58:45

All information / dimensions are approximate, technical changes reserved. © Hupfer