

Fully-welded container transport cart

P/N: 7505985 | CTW/VV 3StE 724/754/1445

HUPFER
we make work flow

Technical data



Cleaning classification:	Waschanlagentauglich
Capacity:	3 × StE
Payload:	150 kg
Width:	724 mm
Depth:	754 mm
Height:	1445 mm

Similar to illustration, technical modifications reserved. Without decoration.

Transport trolley for transport and storage of sterile supplies in containers or baskets.

Einwandiger, allseitig geschlossener Wagenkorpus in vollverschweißter, waschanlagentauglicher Ausführung. Aussteifung des Wagendaches durch Kreuzschlag nach oben. Doppelwandige Flügeltüren mit umlaufenden Dichtungen um 270° zu öffnen, automatische Verschlussmechanik, mit einer Hand bedienbar. Türverschluss durch integrierte 2-Punkt-Verriegelung. Innenraum serienmäßig mit entnehmbaren und auf der kompletten Innenraumhöhe höhenverstellbaren L-Profil-Auflageschienen. Schienen zur Aufnahme von Sterilgutkörben bzw. -containern. Vier senkrecht durchgehende Schubstangen (2 je Seite) zum Manövrieren auch bei geöffneten Türen. Anfahrschutz durch stabile umlaufende Stoßleiste mit stirnseitigen Aussparungen für eventuelle Zugvorrichtung am Fahrwerk, auch bei geöffneten Türen wirksam. Wagen fahrbar auf 2 Lenkrollen mit Totalfeststeller, 2 Bockrollen, mit mehrfach verschraubten Anschraubplatten befestigt.

Time and date of the request:
31.01.2025, 12:55:22

All information / dimensions are approximate, technical changes reserved. © Hupfer