

Hot-Cold-Plate GN-1/1 with glass surface for central refrigeration for installation, without

Technical data



Similar to illustration, technical modifications reserved. Without decoration.

| | |
|--------------------------|--------------|
| Payload: | 9 kg |
| Capacity: | 1840 W |
| Supply voltage: | AC 220-230 V |
| Nominal current: | 8.00 A |
| Protection class: | Klasse 1 |
| Frequency: | 50-60 Hz |
| Weight: | 12.989 kg |
| Width: | 343 mm |
| Depth: | 543 mm |
| Height: | 201 mm |

Hot and cold plate for the presentation and serving of hot and cold food. Device for installation in a counter or mobile bain marie.

High-quality stainless steel unit in stable, self-supporting and hygienic design. A hot and cold plate with a cover plate that ensures optimum temperature distribution due to its excellent temperature distribution is integrated in the cover. The use of a control system with digitally programmable temperatures and cooling pipes for connection to the on-site central cooling system. Self-regulating PTC heating elements with a short heat-up phase and a constant linear temperature curve on the other hand additionally enables a fast change between cold and hot operation in the range from -5°C to +140° C.

Time and date of the request:
20.10.2024, 05:19:53

All information / dimensions are approximate, technical changes reserved. © Hupfer