

## Hot-Cold-Plate GN-3/1 sintered ceramic top for central refrigeration for installation, without

### Technical data



*Similar to illustration, technical modifications reserved. Without decoration.*

<b>Temperature range:</b>	digital controller, precise to the degree
<b>Payload:</b>	27 kg
<b>Capacity:</b>	2070 W
<b>Supply voltage:</b>	AC 220-230 V
<b>Nominal current:</b>	9.00 A
<b>Protection class:</b>	Klasse 1
<b>Frequency:</b>	50-60 Hz
<b>Weight:</b>	26.205 kg
<b>Width:</b>	990 mm
<b>Depth:</b>	543 mm
<b>Height:</b>	201 mm

Hot and cold plate for the presentation and serving of hot and cold food. Device for installation in a counter or mobile bain marie.

High-quality stainless steel unit in stable, self-supporting and hygienic design. A hot and cold plate with a cover plate that ensures optimum temperature distribution due to its excellent temperature distribution is integrated in the cover. The use of a control system with digitally programmable temperatures and cooling pipes for connection to the on-site central cooling system. Self-regulating PTC heating elements with a short heat-up phase and a constant linear temperature curve on the other hand additionally enables a fast change between cold and hot operation in the range from -5°C to +140° C.

Time and date of the request:  
22.12.2024, 12:28:56

*All information / dimensions are approximate, technical changes reserved. © Hupfer*