

## Hot-Cold-Plate GN-4/1 sintered ceramic top with we make work flow cooling unit built-in unit, without frame

## **Technical data**



Similar to illustration, technical modifications reserved. Without decoration.

**Temperature range:** digital controller, precise to the degree

546 mm

 Payload:
 36 kg

 Capacity:
 2420 W

**Supply voltage:** AC 220-230 V

Nominal current: 10.50 A

Protection class: Klasse 1

Frequency: 50-60 Hz

Weight: 33.678 kg

**Width:** 1320 mm

Height: 201 mm

Hot and cold plate for the presentation and serving of hot and cold food. Device for installation in a counter or mobile bain marie.

Depth:

High-quality stainless steel unit in stable, self-supporting and hygienic design. A hot and cold plate with a cover plate that ensures optimum temperature distribution due to its excellent temperature distribution is integrated in the cover. The use of a control system with digitally programmable temperatures and cooling pipes for connection to the on-site central cooling system. Self-regulating PTC heating elements with a short heat-up phase and a constant linear temperature curve on the other hand additionally enables a fast change between cold and hot operation in the range from -5°C to +140°C.

Time and date of the request: 27.09.2024, 13:22:56

All information / dimensions are approximate, technical changes reserved. © Hupfer