


Product



Hot-Cold-Plate GN-4/1, with glass top, for central cooling, built-in

Hot and cold plate for the presentation and serving of hot and cold food. Hot-Cold-Plate for installation in a counter or mobile bain marie.

Features

Time-saving	Fast switching speeds from cold to warm and warm to cold.
Flexible	Versatile use in the action area due to cold and warm temperatures.
Temperature-safe	Digital temperature setting accurate to the degree.
Future-proof	Connection to on-site central refrigeration system (R513a).

Usage & Capacity

Capacity		4x GN-1/1
Usable width	mm	1320
Usable depth	mm	530
Max. load capacity	kg	36
Temperature range	°C	- 5° C bis + 140° C

Equipment

Construction		
Design		Unit in stable, self-supporting and hygienic construction made of high-quality stainless steel. A cold-warm plate with cover plate is integrated into the cover, which provides optimum temperature distribution due to its excellent conductivity.
Surface		with glass top

Technical features

Heating technology		
Heat generation		Self-regulating PTC heating elements with short heat-up phase and constant linear temperature curve.
Heating capacity	W	2420
Cooling technology		
Cooling technology		On-site central cooling
Refrigerant		R513a
Refrigerant, quantity	g	-
Cooling capacity	W	340
Air flow for supply & exhaust air	m³/h	-
Control		
Position		Unit control on a stainless steel panel for installation in an on-site installation compartment or a separately tendered heat/light gantry.
Control operation		Operating and control unit with digital temperature display, main switch (on/off, cold/warm) and buttons for setting the target temperature.
Temperature range		- 5° C bis + 140° C
Connection		Control unit supplied loose with 1.8m connection cable.

Technical Data

Dimensions (approx.)

Width	mm	1320
Depth	mm	530
Height	mm	200

Weight & load capacity (approx.)

Weight, net	kg	41
-------------	----	----

Electrical connection

Electrical voltage	V	230
Electrical connected load	W	2420
Nominal current	A	10,5
Frequency	Hz	50 - 60
Protection class		IPX3 (in installed condition)

Cleaning

Permissible cleaning methods

Manual cleaning	Suitable for manual, damp wipe cleaning. Smooth surfaces on the outside ensure easy and hygienic cleaning.
-----------------	--

Permissible cleaning agents

Suitable for commercially available, grease-dissolving cleaning agents. Use according to the instructions of the cleaning agent manufacturer.

Options for equipment

Mounting frame

Mounting frame	Stainless steel installation frame for flush or surface installation of the cold-warm panel.
Mounting frame	Stainless steel installation frame for flush-mounted or surface-mounted installation of the cold-warm panel and for direct mounting of a Hupfer thermal bridge.

Heated/Light Gantry

Design

Horizon 1	Top frame made of closed sheet metal profiles with 90° angled glass pane 450/100 mm made of Horizon glass type. Height approx. 515 mm above worktop.
Horizon 2	Top frame made of 2 round tubes Ø 25 mm with 90° angled glass pane 450/100 mm made of Horizon glass type. Height approx. 515 mm above worktop.
Optima	Top frame made of round tube Ø 38 mm with curved glass pane, approx. 510 mm deep, made of Optima glass type. Height approx. 565 mm above worktop.

Built-in module

Infrared emitter & LED

Infrared emitter & LED	Built-in module with innovative infrared and light reflector for heating food without scattering losses per GN compartment and LEDs for attractive presentation of cold food. Installed in the top housing of the thermal bridge. Temperature of the touchable surfaces of the thermal bridges max. 50 °C.
Heat output per infrared emitter	W 300
Light colour	K 3000

Brand

Manufacturer	HUPFER Metallwerke GmbH & Co. KG
Model	KWP GN-4/1 GLA ZK EW1
Designation	Hot-Cold-Plate GN-4/1, with glass top, for central cooling, built-in
Item no.	8900257

Document

Document index	1.0
Last change	08.03.2022