

Transport shelving unit

Технические характеристики изделия 0121393 | RTW/Z 12-6/900

HUPFER
we make work flow



Технические характеристики

| | |
|---------------------------|---------|
| Размер ячейки: | 150 mm |
| Полезная нагрузка: | 200 kg |
| Масса: | 18 кг |
| Ширина: | 1275 мм |
| Глубина: | 675 мм |
| Высота: | 900 мм |

Показан пример без декоративных элементов, точность технического описания не гарантируется.

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12" (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded \varnothing 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06" (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, \varnothing 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 12-6/900 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Дата обращения: 05.02.2025,
15:44:20

Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer