

# Transport shelving unit

Технические характеристики изделия 0123094 | RTW/Z 12-5/1652

**HUPFER**  
we make work flow



## Технические характеристики

<b>Размер ячейки:</b>	150 mm
<b>Полезная нагрузка:</b>	200 kg
<b>Масса:</b>	18 кг
<b>Ширина:</b>	1270 мм
<b>Глубина:</b>	570 мм
<b>Высота:</b>	1652 мм

*Показан пример без декоративных элементов, точность технического описания не гарантируется.*

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12" (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0. 28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06" (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 12-5/1652 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Дата обращения: 12.04.2025,  
21:43:22

*Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer*