HUPFER we make work flow

Mobile bain marie for mobile counters

Технические характеристики изделия 0164208 | SPA 3EB LS



Показан пример без декоративных элементов, точность технического описания не гарантируется.

Технические характеристики

Вместимость: 3 × Behälter GN 1/1-200 oder kleiner

Полезная нагрузка: 165 kg **Мощность:** 2100 W

Входное напряжение: AC 220-230 V

Номинальный ток: 9,0 A

Класс защиты: Class I

Частота: 50/60 Hz

Macca: 46 кг

Ширина: 677 мм

Глубина: 1236 мм

Высота: 900 мм

Heated mobile bain-marie for transporting and dispensing prepared food in GN containers, especially for mobile counters.

High-quality stainless steel trolley in stable, self-supporting and hygienic design. Enclosed design with seamlessly welded, fully insulated wells, can be heated wet or dry, with deep drawn level indicator for wet heating. Each well can hold a GN 1/1-200 or smaller container. The wells are specifically sloped at the bottom so that they can be completely drained via an externally adjustable 1/2" ball valve. Drain cock protected from accidental opening, each setting easily visible even at a distance. Heated by stainless steel tubular heating element, can be operated at the side via on/off switch with integrated indicator light and thermostatically controlled by variable, ergonomically designed temperature controller, also easily seen at a distance, with temperature limiter as per VDE. Power supplied by a sturdy retractable helix cable with angle plug and holder on the left narrow side. Firmly welded frame made of rectangular tube with welded-on shelf with all-round edged downfold, with board with circumferential profile edge all round the bottom of the trolley. Four solid polyethylene disc bumpers at the bottom for all-round protection of the device and walls from damage. There is an additional bumper with integrated finger grip above the controls. Trolley on 4 swivel castors, including 2 with total brakes, Ø 125 mm, with pin fixing.

The Hupfer mobile bain marie SPA EB-3 LS is specially equipped with a recessed grip above the operating elements on the long side, and a power feed installed on the front side, for use at docking counters. The Дата обращения: 05.04.2025,

3начения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer



Mobile bain marie for mobile counters

Технические характеристики изделия 0164208 | SPA 3EB LS

installation neight of 900 mm	is the standard working	neight in food distribution.
-------------------------------	-------------------------	------------------------------

Дата обращения: 05.04.2025, 16:21:27 Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer