Swivel castor Ø125 mm



Технические характеристики изделия 0191445141 | LR Poly/St P1/125



Технические характеристики

Полезная нагрузка: 100 kg

Macca: 0.6 кг

Ширина: 148 мм

Глубина: 59 мм

Высота: 165 мм

Показан пример без декоративных элементов, точность технического описания не гарантируется.

The swivel castor with brake is designed for attachment to mobile devices. The swivel castor with brake enables the mobility, steerability, and controllability of the devices.

The easy-running swivel castor with brake made of high-quality plastic and metal parts made of galvanized steel is corrosion-resistant and is designed for attachment to movable equipment. The Hupfer swivel castor ensures the mobility of movable devices. The effortless turning, steering, and positioning of the equipment using the swivel castors increase the efficiency and safety of tasks in tight or crowded work areas. The robust swivel castor is equipped with a swivel bearing with a double ball race and allows for easy handling of the equipment, even with heavy loads. The antistatic tyres prevent electrostatic charging and effectively protect against potential voltage flashes. The plain bearing enables almost silent and smooth mobility. The swivel castor is securely mounted to the device using a mounting plate, ensuring stability.

- Durable plastic housing ensures longevity
- Swivel bearings with double ball ring allow for effortless movement and precise control
- Sliding bearings provide near-silent and smooth operation
- Antistatic tyres prevent electrostatic charging and effectively protect against voltage spikes

Дата обращения: 04.04.2025, 23:56:01

Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer