

Swivel castor with lock Ø 125 mm

Технические характеристики изделия 0191445150 | LR Poly/St Rl1/125



Технические характеристики

Полезная нагрузка: 100 kg

Macca: 0.5 κΓ

Ширина: 130 мм

Глубина: 59 мм

Высота: 161 мм

Показан пример без декоративных элементов, точность технического описания не гарантируется.

The swivel castor with a brake is designed for attachment to mobile devices. The swivel castor with a brake enables the mobility, steerability, and controllability of the devices.

The easy-running swivel castor with brake made of high-quality plastic and metal parts from galvanised steel is corrosion-protected and is designed for attachment to movable equipment. The Hupfer swivel castor ensures the mobility of movable devices. The effortless turning, steering, and positioning of the devices using the swivel castors increase the efficiency and safety of performing tasks in tight or crowded work areas. The robust swivel castor is equipped with a swivel bearing with a double ball race and allows for effortless handling of the equipment, even with heavy loads. The sliding bearing enables almost silent and smooth mobility. The brakes ensure the securing and stabilisation of the device's position. The swivel castor is securely mounted to the device via a rear hole, providing stability.

- Durable plastic housing ensures longevity
- Swivel bearings with double ball race allow effortless movement and precise control
- Plain bearings provide near-silent and smooth operation
- Locking mechanisms guarantee the securing and stabilisation of the device's position

Дата обращения: 04.04.2025, 23:46:59 Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer